

US007500504B2

(12) United States Patent

Bonacini

(10) Patent No.:

US 7,500,504 B2

(45) Date of Patent:

Mar. 10, 2009

(54)	BEAD BREAKING UNIT FOR TIRE
	CHANGING MACHINES

- Maurizio Bonacini, Correggio (IT) (75)Inventor:
- Assignee: Giuliano S.p.A., Correggio (IT)
- Subject to any disclaimer, the term of this (*) Notice: patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

- (21) Appl. No.: 11/892,875
- Filed: Aug. 28, 2007 (22)
- **Prior Publication Data** (65)US 2008/0060762 A1 Mar. 13, 2008
- Foreign Application Priority Data (30)..... MO2006A0274 Sep. 8, 2006
- Int. Cl. (51) (2006.01) B60C 25/135
- U.S. Cl. 157/1.17 (52)
- Field of Classification Search 157/1.17, 157/1.28, 11 See application file for complete search history.

References Cited (56)

U.S. PATENT DOCUMENTS

2/1989 Mandelko 157/1.17 4,804,030 A *

5,226,465 A *	7/1993	Schon et al	157/1.28
6,276,423 B1*	8/2001	Goracy	157/1.17
7,341,090 B2 *	3/2008	Gonzaga	157/1.17

* cited by examiner

Primary Examiner-David B Thomas (74) Attorney, Agent, or Firm-Dykema Gossett PLLC

ABSTRACT (57)

A bead breaking unit includes an arm which is attachable to the base of a tire changing machine and has a first end for attachment of a bead breaking tool and a second end opposite the first. The first end is mobile between an idle position, in which the bead breaking tool is placed away from the base, and a working position, in which the bead breaking tool is placed in contact with a wheel to bead break, positioned in proximity to the base. The bead breaking unit also includes an adjustment device for adjusting the trajectory of the bead breaking tool when moving between the idle position and the working position, which are interposed between the base and the arm and suitable for defining a first operating configuration in which the trajectory is curvilinear and a second operating configuration in which the trajectory is rectilinear.

9 Claims, 3 Drawing Sheets

